

# sustain 1195



## marmoleum<sup>®</sup> sheet & tile adhesive

### Performance

- Water-based adhesive - 100% solvent free
- Highly Moisture Resistant - 10 lbs. per 1,000 square feet in 24 hours when tested in accordance with the latest version of ASTM F1869, and 95% RH when tested with the latest version of ASTM F2170. Surface pH of concrete slabs must not exceed a pH of 11.
- Contains MicroSept™ Anti-Microbial Protection
- CA SCAQMD Rule 1168 Compliant
- Passes Air Quality Regulations per CA Section 01350
- Use a 1/16" x 1/16" x 1/16" Square Notch Trowel
- Spread Rate: Approximately 125 square feet per gallon



### Sustainability

- Contains 25% Post-Consumer Recycled Content
- Packaged in biodegradable plastic pails, which decompose naturally in landfills within 1 - 3 years.
- Sustain 1195 contributes to LEED™ V4 points in the following categories:
  - EQc2 – low emitting materials
  - MRc4 – building product disclosure and optimization - sourcing of raw materials
  - MRp2 – construction and demolition waste management



## sustain (sə-'stān)



1-800-842-7839 United States  
1-800-268-8108 Canada  
info.na@forbo.com  
www.forboflooringNA.com

creating better environments

EcoPure<sup>®</sup>  
Biodegradable Plastic Pail

forbo  
FLOORING SYSTEMS