



ECOS INTERIOR FLOOR PAINT APPLICATION INSTRUCTIONS

Recommended For	Use on bare and previously painted wood and concrete floors
Coverage	400 sq. ft. per gallon 100 sq. ft. per quart; 3 coats recommended
Description	Interior Floor Paint is a high sheen, protective finish that dries to a hard, washable, durable film that resists cracking and peeling. Ideal for interior wooden floors and dry concrete. Not recommended for oily woods such as teak, rosewood, and olive, or areas subject to wetting.
Preparation	Surfaces should be clean, dry, sound, and free from dirt, dust, grease, and loose or flaking material. Clean stubborn areas with mild detergent. Rinse and dry thoroughly before painting. Unpainted (or unfinished) surfaces should first be primed to ensure an even base color and consistency, before applying the paint.
Application and Clean Up	Under most conditions thinning is not necessary. Stir gently before and during use. Intermix if using multiple containers to ensure color uniformity. Best results are achieved with three coats. Typically dries to the touch in two hours and can be recoated in twenty four. Hardening continues for up to thirty days. Avoid wetting, or scuffing during this period. Can be applied using a good quality synthetic brush; or rolled using a shed resistant 3/8"-1/2" roller cover. Avoid applying below 50°F (10°C).