



ECOS INTERIOR WALL & CEILING PAINT - EGGSHELL APPLICATION INSTRUCTIONS

Recommended For	Walls & ceilings; ideal for kitchens, bathrooms, and other high-moisture and high-traffic areas
Coverage	560 sq. ft. per gallon 140 sq. ft. per quart; 2 coats recommended
Description	Eggshell Paint is a medium sheen, protective finish that dries to a hard, durable, film. Ideal for interior walls & ceilings including kitchens, bathrooms, and other high-moisture or high-traffic areas. Hard-wearing and highly washable.
Preparation	Good surface preparation is vital for the perfect finish. Surfaces should be clean, dry, and free from any dirt, dust, or contaminants. Repair any cracks, holes, or imperfections. Sand glossy surfaces with fine grit sandpaper first to ensure good adhesion. Before painting, clean stubborn areas with mild detergent, and remove any loose, or peeling paint, then rinse and dry thoroughly before painting. We recommend using one of our primers if painting over a higher gloss finish, a darker color, or applying an accent color, or applying over bare or heavily sanded surfaces.
Application and Clean Up	<p>Stir well before use. If using multiple containers of the same color, intermix them all to ensure color uniformity. Can be applied using a high quality synthetic brush, rolled using a shed-resistant 3/8" to 1/2" roller cover, or sprayed using an airless sprayer with 0.015" to 0.017" tip at 1600 to 1800 psi. Do not apply in temperatures below 50°F (10°C). For best results, always apply two coats of paint. Dries to the touch in 30 to 60 minutes.</p> <p>Recommended wait time between coats is 2 to 4 hours. High humidity and cool temperatures may result in longer dry and recoat times. Do not thin the paint. Clean up with warm soapy water.</p>