



## ECOS WOOD PRIMER APPLICATION INSTRUCTIONS

<b>Recommended For</b>	Wooden floors, windows, doors, trim, furniture, cabinets, and other woodwork
<b>Coverage</b>	400 sq. ft. per gallon   100 sq. ft. per quart; 1 coat recommended
<b>Description</b>	Wood Primer provides a strong bonding surface for paint and adds an extra layer of protection to your woodwork. Ideal for windows, doors, trim, furniture, cabinets, and other interior and exterior woodwork. Before painting a wooden floor, wood primer is highly recommended, especially if the floor is not waterproof, can't be cleaned, or is made of porous materials. Wood primer ensures that a surface is sealed and protected before being painted.
<b>Preparation</b>	Surfaces should be clean, dry, sound, and free from dirt, dust, grease, and loose or flaking material. Clean stubborn areas with mild detergent. Rinse and dry thoroughly before painting. Soft or crumbly substrates should be pre-treated.
<b>Application and Clean Up</b>	Under most conditions, thinning is not necessary. Stir gently before and during use. Intermix if using multiple containers to ensure color uniformity. Generally only requires one coat. Sand lightly between coats as this product may raise the grain of the wood. Normally dries to the touch in four hours. Allow twenty four hours before sanding or painting. Can be applied using a good quality synthetic brush; or rolled using a shed resistant 1/4"-3/8" roller cover. Avoid applying below 50°F (10°C).