



SPECIFICATION

CORK UNDERLAYMENT 6MM

Cork is recognized as some of the most effective sound control and crack suppression underlayment used under hardwood, laminate and ceramic floors.

FEATURES

- Excellent sound suppression that is shock / impact absorbing for an acoustically pleasing underlayment.
- Provides additional thermal insulation beneath surface flooring materials for comfortability underfoot.
- Homogenous 100% quercus suber cork composition.
- Naturally antimicrobial, bacteria and spore-resistant and insect repellent.
- Made with recycled content and rapidly renewable materials.

SUGGESTED APPLICATIONS

Hospitality	Corporate
Senior Living	Multi-family

APPROVED ADHESIVES

All Shaw Resilient / Wood Adhesives.

SPECIFICATIONS



Style name	Cork Underlayment	
Warranty	Shaw Underlayment Limited Warranty	
Roll size	U.S. 48" x 50' / 200 sq ft	Metric 15.24 m x 1.219 m x 6 mm
Thickness	0.252 in	6.4 mm
Density	11.7 lb/ft ³ - 12.5 lb/ft ³	187.416 kg/m ³ - 200.23 kg/m ³
Installation method	Glue down	

impact insulation class rating: IIC (ASTM E492-09/E989-06) When paired with the appropriate resilient flooring, results typically range from 50 -70, depending on subfloor assembly and resilient product. For specific results, please contact your account manager.